

LEADWELL®

LTC-20D SERIES





FEAUTURES:

MORE POWERFUL

- *Powerful main spindle 20HP
- *Rigid 30 deg. Slant bed cast iron base

INCREASED CAPACITY

- *8 inch chuck standard
- *65mm bar capacity standard

FASTER/MORE PORDUCTIVE

- *Fast rapid rates 20~30m/min
- *Spindle speed 4000rpm

ERGONOMIC CONSIDERSATIONS

- *Easy to use membrane touch-pad control station
- *Easy moving operator door
- *Parts catcher available
- *No chip or coolant leaks

Specifications

Item		LTC-20D	LTC-20DM	LTC-20DMY
Max. swing	mm (in)	500(19.7)	540(21.2)	570(22.4)
Max. turning diameter	mm (in)	380(15)	320(12.6)	320(12.6)
Max. turning length	mm (in)	500(19.7)	430(16.9)	458(18)



Bar capacity	mm (in)	65(2.6)	65(2.6)	65(2.6)
X axis travel	mm (in)	190+20(7.5+0.8)	160+20(6.3+0.8)	160+35(6.2+1.37)
Z axis travel	mm (in)	540(21.3)	540(21.3)	510(20)
Spindle speeds range	rpm	4000	4000	4000
Chuck size	mm (in)	8	8	8